



FULL DEPTH STONE TO BE MAINTAINED
UNTIL ASPHALT PATCHING OCCURS.
MINIMUM 95% STD PROCTOR DENSITY
REQUIRED TO PATCH.
ONE YEAR WARRANTY APPLIES AFTER
DATE OF PATCHING. UTILITY
COMPANY CONTRACTOR RESPONSIBLE
FOR WARRANTY REPAIR.

Utility cuts on NCDOT maintained roads shall be repaired per NCDOT Drawing 654.01, Sht. 2 of 2, and these materials should be compacted to within 95% of standard proctor. Said cuts should be patched with asphalt surface material, also according to (71D-26) on the same day as the cut is made.

Within the twelve months following the street cut, the City will periodically check these patches for integrity. If any further action is needed, the City will inform the appropriate Utility, who will then be responsible for making any and all necessary repairs.

REVISED	F.B.	PG.	DATE: 31 JAN, 1974
1/24/89			SCALE: NONE
9/12/94			DRAWN BY: DNC, DYS, EZ
1/05/95			CHECKED BY: NBM, FAP
5/29/97			CITY ENGINEER: JPB
2/2/01	5/27/05		

STANDARD DETAIL

TYPICAL PAVEMENT REPAIR
FOR UTILITIES CUT (NCDOT)
(FOR THOROUGHFARES OR INDUSTRIAL)

OFFICE OF THE
CITY ENGINEER
GASTONIA, N.C.

FILE
NO. **71D-26**